



**PRODUCT DESCRIPTION** Liquid Electrical Tape is a quick drying black coating for wiring and electrical connections. It creates a continuous waterproof seal that prevents corrosion and remains flexible when dry.

**PRODUCT BENEFITS**

- Provides a flexible coating for electrical wiring
- Permits flow of electrical current
- Waterproof- prevents moisture and corrosion
- Eliminates the need for electric tape or shrink tubing
- Remains flexible after curing
- UV resistant

**TYPICAL APPLICATIONS**

- Underground wiring
- Outdoor lighting fixtures
- Bilge pumps
- Terminal blocks
- Exposed wires

**DIRECTIONS FOR USE**

1. For best results, avoid direct sunlight, high humidity or windy conditions.
2. Always disconnect power before applying.
4. Stir well before using.
5. Make sure surfaces are clean and dry.
6. Apply liquid tape to connection or repair area.
7. Allow 10 minutes minimum between coats. A minimum of two coats is recommended.
8. Allow 4 hours minimum dry time before use.
9. Allow Liquid Electrical Tape to dry completely before restoring power.

**STORAGE**

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8 C and 28C

**PHYSICAL PROPERTIES OF MATERIAL**

Chemical Type	Proprietary compound
Appearance	Black liquid
Specific Gravity	0.97
Flash Point, SCC C (F)	16 (60)
Temperature Range	F(C) -65 to 400 (-54 to 204)
Dielectric Strength, ASTM D-149	1117 volts/mil (6.3 mil thickness)

[WWW.GROUPGSHK.COM](http://WWW.GROUPGSHK.COM)